

**Your partner  
for production efficiency**

## High performing elastomer conveyor belt 3M8 U0-U-G5 HS FL




HS<sup>®</sup> elastomer superior properties combined with a 3-ply construction assure **highest production efficiency and long service life.**

Ideal for **vacuum** conveying in Paper&Printing and Wood processing.

KEY FEATURES	BENEFITS
3-ply construction assures excellent planarity	▶ <b>Perfect product position No product slippage</b>
HS <sup>®</sup> cover offers high abrasion resistance	▶ <b>Long service life</b>



 <b>Unique high performing elastomer</b>	▶ <b>High abrasion resistance.</b> The unique HS <sup>®</sup> cover provides an excellent abrasion resistance and a uniform coefficient of friction over time.
	▶ <b>Excellent resilience.</b> The unique HS <sup>®</sup> properties offer outstanding resilience, high elasticity and resistance to cracking.
	▶ <b>Long service life.</b> The low aging property of the HS <sup>®</sup> cover provides a long service life and optimized cost of ownership.

Code	Type	Conveying surface coating		Permanent antistatic	Total thickness mm	Min. diameter mm	Pull for 1% elongation N/mm	Temperature resistance °C	
		material	colour					min.	max.
NA-1146	<b>3M8 U0-U-G5 HS FL</b>	HS <sup>®</sup> elastomer	green	yes	3.0	60	10	-20	100